

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 12.0                  | 0.5                 | 0.142                 |
| 12.0                  | 0.6                 | 0.169                 |
| 12.0                  | 0.8                 | 0.221                 |
| 12.0                  | 1                   | 0.271                 |
| 12.0                  | 1.2                 | 0.320                 |
| 12.0                  | 1.4                 | 0.366                 |
| 12.0                  | 1.6                 | 0.410                 |
| 12.0                  | 1.8                 | 0.453                 |
| 12.0                  | 2.0                 | 0.493                 |
| 12.0                  | 2.3                 | 0.550                 |
| 12.0                  | 2.6                 | 0.603                 |
| 12.0                  | 2.9                 | 0.651                 |
| 12.0                  | 3.2                 | 0.694                 |
| 12.7                  | 0.5                 | 0.150                 |
| 12.7                  | 0.6                 | 0.179                 |
| 12.7                  | 0.8                 | 0.235                 |
| 12.7                  | 1                   | 0.289                 |
| 12.7                  | 1.2                 | 0.340                 |
| 12.7                  | 1.4                 | 0.390                 |
| 12.7                  | 1.6                 | 0.438                 |
| 12.7                  | 1.8                 | 0.484                 |
| 12.7                  | 2.0                 | 0.528                 |
| 12.7                  | 2.3                 | 0.590                 |
| 12.7                  | 2.6                 | 0.648                 |
| 12.7                  | 2.9                 | 0.701                 |
| 12.7                  | 3.2                 | 0.750                 |
| 16.0                  | 0.5                 | 0.191                 |
| 16.0                  | 0.6                 | 0.228                 |
| 16.0                  | 0.8                 | 300                   |
| 16.0                  | 1                   | 370                   |
| 16.0                  | 1.2                 | 438                   |
| 16.0                  | 1.4                 | 0.504                 |
| 16.0                  | 1.6                 | 0.568                 |
| 16.0                  | 1.8                 | 0.63                  |
| 16.0                  | 2.0                 | 0.691                 |
| 16.0                  | 2.3                 | 0.777                 |
| 16.0                  | 2.6                 | 0.859                 |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 16.0                  | 2.9                 | 0.937                 |
| 16.0                  | 3.2                 | 1.01                  |
| 16.0                  | 3.6                 | 1.10                  |
| 16.0                  | 4                   | 1.18                  |
| 19.0                  | 0.5                 | 0.228                 |
| 19.0                  | 0.6                 | 0.272                 |
| 19.0                  | 0.8                 | 0.359                 |
| 19.0                  | 1                   | 0.444                 |
| 19.0                  | 1.2                 | 0.527                 |
| 19.0                  | 1.4                 | 0.608                 |
| 19.0                  | 1.6                 | 0.687                 |
| 19.0                  | 1.8                 | 0.764                 |
| 19.0                  | 2.0                 | 0.838                 |
| 19.0                  | 2.3                 | 0.947                 |
| 19.0                  | 2.6                 | 1.05                  |
| 19.0                  | 2.9                 | 1.15                  |
| 19.0                  | 3.2                 | 1.25                  |
| 19.0                  | 3.6                 | 1.37                  |
| 19.0                  | 4                   | 1.48                  |
| 19.0                  | 4.5                 | 1.61                  |
| 19.0                  | 5                   | 1.73                  |
| 20.0                  | 0.5                 | 0.240                 |
| 20.0                  | 0.6                 | 0.287                 |
| 20.0                  | 0.8                 | 0.379                 |
| 20.0                  | 1                   | 0.469                 |
| 20.0                  | 1.2                 | 0.556                 |
| 20.0                  | 1.4                 | 0.642                 |
| 20.0                  | 1.6                 | 0.726                 |
| 20.0                  | 1.8                 | 0.808                 |
| 20.0                  | 2.0                 | 0.888                 |
| 20.0                  | 2.3                 | 1.00                  |
| 20.0                  | 2.6                 | 1.12                  |
| 20.0                  | 2.9                 | 1.22                  |
| 20.0                  | 3.2                 | 1.33                  |
| 20.0                  | 3.6                 | 1.46                  |
| 20.0                  | 4                   | 1.58                  |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 20.0                  | 4.5                 | 1.72                  |
| 20.0                  | 5                   | 1.85                  |
| 25.0                  | 0.5                 | 0.302                 |
| 25.0                  | 0.6                 | 0.361                 |
| 25.0                  | 0.8                 | 0.477                 |
| 25.0                  | 1                   | 0.592                 |
| 25.0                  | 1.2                 | 0.704                 |
| 25.0                  | 1.4                 | 0.815                 |
| 25.0                  | 1.6                 | 0.923                 |
| 25.0                  | 1.8                 | 1.03                  |
| 25.0                  | 2.0                 | 1.13                  |
| 25.0                  | 2.3                 | 1.29                  |
| 25.0                  | 2.6                 | 1.44                  |
| 25.0                  | 2.9                 | 1.58                  |
| 25.0                  | 3.2                 | 1.72                  |
| 25.0                  | 3.6                 | 1.90                  |
| 25.0                  | 4                   | 2.07                  |
| 25.0                  | 4.5                 | 2.28                  |
| 25.0                  | 5                   | 2.47                  |
| 25.0                  | 5.4                 | 2.61                  |
| 25.0                  | 5.6                 | 2.68                  |
| 25.0                  | 6.3                 | 2.91                  |
| 31.8                  | 0.5                 | 0.386                 |
| 31.8                  | 0.6                 | 0.462                 |
| 31.8                  | 0.8                 | 0.612                 |
| 31.8                  | 1                   | 0.760                 |
| 31.8                  | 1.2                 | 0.906                 |
| 31.8                  | 1.4                 | 1.05                  |
| 31.8                  | 1.6                 | 1.19                  |
| 31.8                  | 1.8                 | 1.33                  |
| 31.8                  | 2.0                 | 1.47                  |
| 31.8                  | 2.3                 | 1.67                  |
| 31.8                  | 2.6                 | 1.87                  |
| 31.8                  | 2.9                 | 2.07                  |
| 31.8                  | 3.2                 | 2.26                  |
| 31.8                  | 3.6                 | 2.50                  |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 31.8                  | 4                   | 2.74                  |
| 31.8                  | 4.5                 | 3.03                  |
| 31.8                  | 5                   | 3.30                  |
| 31.8                  | 5.4                 | 3.52                  |
| 31.8                  | 5.6                 | 3.62                  |
| 31.8                  | 6.3                 | 3.96                  |
| 31.8                  | 7.1                 | 4.32                  |
| 31.8                  | 8                   | 4.70                  |
| 32.0                  | 0.5                 | 0.388                 |
| 32.0                  | 0.6                 | 0.465                 |
| 32.0                  | 0.8                 | 0.616                 |
| 32.0                  | 1                   | 0.765                 |
| 32.0                  | 1.2                 | 0.911                 |
| 32.0                  | 1.4                 | 1.06                  |
| 32.0                  | 1.6                 | 1.20                  |
| 32.0                  | 1.8                 | 1.34                  |
| 32.0                  | 2.0                 | 1.48                  |
| 32.0                  | 2.3                 | 1.68                  |
| 32.0                  | 2.6                 | 1.89                  |
| 32.0                  | 2.9                 | 2.08                  |
| 32.0                  | 3.2                 | 2.27                  |
| 32.0                  | 3.6                 | 2.52                  |
| 32.0                  | 4                   | 2.76                  |
| 32.0                  | 4.5                 | 3.05                  |
| 32.0                  | 5                   | 3.33                  |
| 32.0                  | 5.4                 | 3.54                  |
| 32.0                  | 5.6                 | 3.65                  |
| 32.0                  | 6.3                 | 3.99                  |
| 32.0                  | 7.1                 | 4.36                  |
| 32.0                  | 8                   | 4.74                  |
| 38.0                  | 0.5                 | 0.462                 |
| 38.0                  | 0.6                 | 0.553                 |
| 38.0                  | 0.8                 | 0.734                 |
| 38.0                  | 1                   | 0.912                 |
| 38.0                  | 1.2                 | 1.09                  |
| 38.0                  | 1.4                 | 1026                  |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 38.0                  | 1.6                 | 1.44                  |
| 38.0                  | 1.8                 | 1.61                  |
| 38.0                  | 2.0                 | 1.78                  |
| 38.0                  | 2.3                 | 2.02                  |
| 38.0                  | 2.6                 | 2.27                  |
| 38.0                  | 2.9                 | 2.51                  |
| 38.0                  | 3.2                 | 2.75                  |
| 38.0                  | 3.6                 | 3.05                  |
| 38.0                  | 4                   | 3.35                  |
| 38.0                  | 4.5                 | 3.72                  |
| 38.0                  | 5                   | 4.07                  |
| 38.0                  | 5.4                 | 4.34                  |
| 38.0                  | 5.6                 | 4.47                  |
| 38.0                  | 6.3                 | 4.93                  |
| 38.0                  | 7.1                 | 5.41                  |
| 38.0                  | 8.0                 | 5.92                  |
| 38.0                  | 8.8                 | 6.34                  |
| 38.0                  | 10                  | 6.91                  |
| 40.0                  | 0.5                 | 0.487                 |
| 40.0                  | 0.6                 | 0.583                 |
| 40.0                  | 0.8                 | 0.773                 |
| 40.0                  | 1                   | 0.962                 |
| 40.0                  | 1.2                 | 1.15                  |
| 40.0                  | 1.4                 | 1.33                  |
| 40.0                  | 1.6                 | 1.52                  |
| 40.0                  | 1.8                 | 1.70                  |
| 40.0                  | 2.0                 | 1.87                  |
| 40.0                  | 2.3                 | 2.14                  |
| 40.0                  | 2.6                 | 2.40                  |
| 40.0                  | 2.9                 | 2.65                  |
| 40.0                  | 3.2                 | 2.90                  |
| 40.0                  | 3.6                 | 3.23                  |
| 40.0                  | 4                   | 3.55                  |
| 40.0                  | 4.5                 | 3.94                  |
| 40.0                  | 5                   | 4.32                  |
| 40.0                  | 5.4                 | 4.61                  |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 40.0                  | 5.6                 | 4.75                  |
| 40.0                  | 6.3                 | 5.24                  |
| 40.0                  | 7.1                 | 5.76                  |
| 40.0                  | 8.0                 | 6.31                  |
| 40.0                  | 8.8                 | 6.77                  |
| 40.0                  | 10                  | 7.4                   |
| 51.0                  | 0.6                 | 0.746                 |
| 51.0                  | 0.8                 | 0.990                 |
| 51.0                  | 1                   | 1.23                  |
| 51.0                  | 1.2                 | 1.47                  |
| 51.0                  | 1.4                 | 1.71                  |
| 51.0                  | 1.6                 | 1.95                  |
| 51.0                  | 1.8                 | 2.18                  |
| 51.0                  | 2.0                 | 2.42                  |
| 51.0                  | 2.3                 | 2.76                  |
| 51.0                  | 2.6                 | 3.10                  |
| 51.0                  | 2.9                 | 3.44                  |
| 51.0                  | 3.2                 | 3.77                  |
| 51.0                  | 3.6                 | 4.21                  |
| 51.0                  | 4                   | 4.64                  |
| 51.0                  | 4.5                 | 5.16                  |
| 51.0                  | 5                   | 5.67                  |
| 51.0                  | 5.4                 | 6.07                  |
| 51.0                  | 5.6                 | 6.27                  |
| 51.0                  | 6.3                 | 6.94                  |
| 51.0                  | 7.1                 | 7.69                  |
| 51.0                  | 8                   | 8.48                  |
| 51.0                  | 8.8                 | 9.16                  |
| 51.0                  | 10                  | 10.1                  |
| 51.0                  | 11                  | 10.9                  |
| 51.0                  | 12.5                | 11.9                  |
| 57.0                  | 0.6                 | 0.835                 |
| 57.0                  | 0.8                 | 1.11                  |
| 57.0                  | 1                   | 1.38                  |
| 57.0                  | 1.2                 | 1.65                  |
| 57.0                  | 1.4                 | 1.92                  |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 57.0                  | 1.6                 | 2.19                  |
| 57.0                  | 1.8                 | 2.45                  |
| 57.0                  | 2.0                 | 2.71                  |
| 57.0                  | 2.3                 | 3.10                  |
| 57.0                  | 2.6                 | 3.49                  |
| 57.0                  | 2.9                 | 3.87                  |
| 57.0                  | 3.2                 | 4.25                  |
| 57.0                  | 3.6                 | 4.74                  |
| 57.0                  | 4                   | 5.23                  |
| 57.0                  | 4.5                 | 5.83                  |
| 57.0                  | 5                   | 6.41                  |
| 57.0                  | 5.4                 | 6.87                  |
| 57.0                  | 5.6                 | 7.10                  |
| 57.0                  | 6.3                 | 7.88                  |
| 57.0                  | 7.1                 | 8.74                  |
| 57.0                  | 8                   | 9.67                  |
| 57.0                  | 8.8                 | 10.5                  |
| 57.0                  | 10                  | 11.6                  |
| 57.0                  | 11                  | 12.5                  |
| 57.0                  | 12.5                | 13.7                  |
| 57.0                  | 14.2                | 15.0                  |
| 63.5                  | 0.6                 | 0.931                 |
| 63.5                  | 0.8                 | 1.24                  |
| 63.5                  | 1                   | 1.54                  |
| 63.5                  | 1.2                 | 1.84                  |
| 63.5                  | 1.4                 | 2.14                  |
| 63.5                  | 1.6                 | 2.44                  |
| 63.5                  | 1.8                 | 2.74                  |
| 63.5                  | 2.0                 | 3.03                  |
| 63.5                  | 2.3                 | 3.47                  |
| 63.5                  | 2.6                 | 3.90                  |
| 63.5                  | 2.9                 | 4.33                  |
| 63.5                  | 3.2                 | 4.76                  |
| 63.5                  | 3.6                 | 5.32                  |
| 63.5                  | 4                   | 5.87                  |
| 63.5                  | 4.5                 | 6.55                  |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 63.5                  | 5                   | 7.21                  |
| 63.5                  | 5.4                 | 7.74                  |
| 63.5                  | 5.6                 | 8.00                  |
| 63.5                  | 6.3                 | 8.89                  |
| 63.5                  | 7.1                 | 9.88                  |
| 63.5                  | 8                   | 10.9                  |
| 63.5                  | 8.8                 | 11.9                  |
| 63.5                  | 10                  | 13.2                  |
| 63.5                  | 11                  | 14.2                  |
| 63.5                  | 12.5                | 15.7                  |
| 63.5                  | 14.2                | 17.3                  |
| 63.5                  | 16                  | 18.7                  |
| 70.0                  | 0.8                 | 1.37                  |
| 70.0                  | 1                   | 1.70                  |
| 70.0                  | 1.2                 | 2.04                  |
| 70.0                  | 1.4                 | 2.37                  |
| 70.0                  | 1.6                 | 2.70                  |
| 70.0                  | 1.8                 | 3.03                  |
| 70.0                  | 2.0                 | 3.35                  |
| 70.0                  | 2.3                 | 3.84                  |
| 70.0                  | 2.6                 | 4.32                  |
| 70.0                  | 2.9                 | 4.80                  |
| 70.0                  | 3.2                 | 5.27                  |
| 70.0                  | 3.6                 | 5.90                  |
| 70.0                  | 4                   | 6.51                  |
| 70.0                  | 4.5                 | 7.27                  |
| 70.0                  | 5                   | 8.01                  |
| 70.0                  | 5.4                 | 8.60                  |
| 70.0                  | 5.6                 | 8.89                  |
| 70.0                  | 6.3                 | 9.90                  |
| 70.0                  | 7.1                 | 11.0                  |
| 70.0                  | 8                   | 12.2                  |
| 70.0                  | 8.8                 | 13.3                  |
| 70.0                  | 10                  | 14.8                  |
| 70.0                  | 11                  | 16.0                  |
| 70.0                  | 12.5                | 17.7                  |



Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 70.0                  | 14.2                | 19.5                  |
| 70.0                  | 16                  | 21.3                  |
| 70.0                  | 17.5                | 22.7                  |
| 101.6                 | 1.2                 | 2.97                  |
| 101.6                 | 1.4                 | 3.46                  |
| 101.6                 | 1.6                 | 3.95                  |
| 101.6                 | 1.8                 | 4.43                  |
| 101.6                 | 2.0                 | 4.91                  |
| 101.6                 | 2.3                 | 5.63                  |
| 101.6                 | 2.6                 | 6.35                  |
| 101.6                 | 2.9                 | 7.06                  |
| 101.6                 | 3.2                 | 7.77                  |
| 101.6                 | 3.6                 | 8.70                  |
| 101.6                 | 4                   | 9.63                  |
| 101.6                 | 4.5                 | 10.8                  |
| 101.6                 | 5                   | 11.9                  |
| 101.6                 | 5.4                 | 12.8                  |
| 101.6                 | 5.6                 | 13.3                  |
| 101.6                 | 6.3                 | 14.8                  |
| 101.6                 | 7.1                 | 16.5                  |
| 101.6                 | 8                   | 18.5                  |
| 101.6                 | 8.8                 | 20.1                  |
| 101.6                 | 10                  | 22.6                  |
| 101.6                 | 11                  | 24.6                  |
| 101.6                 | 12.5                | 27.5                  |
| 101.6                 | 14.2                | 30.6                  |
| 101.6                 | 16                  | 33.8                  |
| 101.6                 | 17.5                | 36.3                  |
| 101.6                 | 20                  | 40.2                  |
| 101.6                 | 22.2                | 43.5                  |
| 101.6                 | 25                  | 47.2                  |
| 101.6                 | 28                  | 50.8                  |
| 127.0                 | 1.6                 | 4.95                  |
| 127.0                 | 1.8                 | 5.56                  |
| 127.0                 | 2.0                 | 6.17                  |
| 127.0                 | 2.3                 | 7.07                  |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 127.0                 | 2.6                 | 7.98                  |
| 127.0                 | 2.9                 | 8.88                  |
| 127.0                 | 3.2                 | 9.77                  |
| 127.0                 | 3.6                 | 11.0                  |
| 127.0                 | 4                   | 12.1                  |
| 127.0                 | 4.5                 | 13.6                  |
| 127.0                 | 5                   | 15.0                  |
| 127.0                 | 5.4                 | 16.2                  |
| 127.0                 | 5.6                 | 16.8                  |
| 127.0                 | 6.3                 | 18.8                  |
| 127.0                 | 7.1                 | 21.0                  |
| 127.0                 | 8                   | 23.5                  |
| 127.0                 | 8.8                 | 25.7                  |
| 127.0                 | 10                  | 28.9                  |
| 127.0                 | 11                  | 31.5                  |
| 127.0                 | 12.5                | 35.3                  |
| 127.0                 | 14.2                | 39.5                  |
| 127.0                 | 16                  | 43.8                  |
| 127.0                 | 17.5                | 47.3                  |
| 127.0                 | 20                  | 52.8                  |
| 127.0                 | 22.2                | 57.4                  |
| 127.0                 | 25                  | 62.9                  |
| 127.0                 | 28                  | 68.4                  |
| 127.0                 | 30                  | 71.8                  |
| 127.0                 | 32                  | 75.0                  |
| 127.0                 | 36                  | 80.8                  |
| 133.0                 | 1.6                 | 5.18                  |
| 133.0                 | 1.8                 | 5.82                  |
| 133.0                 | 2.0                 | 6.46                  |
| 133.0                 | 2.3                 | 7.41                  |
| 133.0                 | 2.6                 | 8.36                  |
| 133.0                 | 2.9                 | 9.3                   |
| 133.0                 | 3.2                 | 10.2                  |
| 133.0                 | 3.6                 | 11.5                  |
| 133.0                 | 4                   | 12.7                  |
| 133.0                 | 4.5                 | 14.3                  |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 133.0                 | 5                   | 15.8                  |
| 133.0                 | 5.4                 | 17.0                  |
| 133.0                 | 5.6                 | 17.6                  |
| 133.0                 | 6.3                 | 19.7                  |
| 133.0                 | 7.1                 | 22.0                  |
| 133.0                 | 8                   | 24.7                  |
| 133.0                 | 8.8                 | 27.0                  |
| 133.0                 | 10                  | 30.3                  |
| 133.0                 | 11                  | 33.1                  |
| 133.0                 | 12.5                | 37.1                  |
| 133.0                 | 14.2                | 41.6                  |
| 133.0                 | 16                  | 46.2                  |
| 133.0                 | 17.5                | 49.8                  |
| 133.0                 | 20                  | 55.7                  |
| 133.0                 | 22.2                | 60.7                  |
| 133.0                 | 25                  | 66.6                  |
| 133.0                 | 28                  | 72.5                  |
| 133.0                 | 30                  | 76.2                  |
| 133.0                 | 32                  | 79.7                  |
| 133.0                 | 36                  | 86.1                  |
| 762                   | 4                   | 74.8                  |
| 762                   | 4.5                 | 84.1                  |
| 762                   | 5                   | 93.3                  |
| 762                   | 5.4                 | 101                   |
| 762                   | 5.6                 | 104                   |
| 762                   | 6.3                 | 117                   |
| 762                   | 7.1                 | 132                   |
| 762                   | 8                   | 149                   |
| 762                   | 8.8                 | 163                   |
| 762                   | 10                  | 185                   |
| 762                   | 11                  | 204                   |
| 762                   | 12.5                | 231                   |
| 762                   | 14.2                | 262                   |
| 762                   | 16                  | 294                   |
| 762                   | 17.5                | 321                   |
| 762                   | 20                  | 366                   |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 762                   | 22.2                | 405                   |
| 762                   | 25                  | 454                   |
| 762                   | 28                  | 507                   |
| 762                   | 30                  | 542                   |
| 762                   | 32                  | 576                   |
| 762                   | 36                  | 645                   |
| 762                   | 40                  | 712                   |
| 762                   | 45                  | 796                   |
| 762                   | 50                  | 878                   |
| 762                   | 55                  | 959                   |
| 762                   | 60                  | 1039                  |
| 762                   | 65                  | 1117                  |
| 1168                  | 5                   | 143                   |
| 1168                  | 5.4                 | 155                   |
| 1168                  | 5.6                 | 161                   |
| 1168                  | 6.3                 | 180                   |
| 1168                  | 7.1                 | 203                   |
| 1168                  | 8                   | 229                   |
| 1168                  | 8.8                 | 252                   |
| 1168                  | 10                  | 286                   |
| 1168                  | 11                  | 314                   |
| 1168                  | 12.5                | 356                   |
| 1168                  | 14.2                | 404                   |
| 1168                  | 16                  | 455                   |
| 1168                  | 17.5                | 497                   |
| 1168                  | 20                  | 566                   |
| 1168                  | 22.2                | 627                   |
| 1168                  | 25                  | 705                   |
| 1168                  | 28                  | 787                   |
| 1168                  | 30                  | 842                   |
| 1168                  | 32                  | 896                   |
| 1168                  | 36                  | 1005                  |
| 1168                  | 40                  | 1113                  |
| 1168                  | 45                  | 1246                  |
| 1168                  | 50                  | 1379                  |
| 1168                  | 55                  | 1510                  |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 1168                  | 60                  | 1639                  |
| 1168                  | 65                  | 1768                  |
| 1321                  | 5.6                 | 182                   |
| 1321                  | 6.3                 | 204                   |
| 1321                  | 7.1                 | 230                   |
| 1321                  | 8                   | 259                   |
| 1321                  | 8.8                 | 285                   |
| 1321                  | 10                  | 323                   |
| 1321                  | 11                  | 355                   |
| 1321                  | 12.5                | 403                   |
| 1321                  | 14.2                | 458                   |
| 1321                  | 16                  | 515                   |
| 1321                  | 17.5                | 563                   |
| 1321                  | 20                  | 642                   |
| 1321                  | 22.2                | 711                   |
| 1321                  | 25                  | 799                   |
| 1321                  | 28                  | 893                   |
| 1321                  | 30                  | 955                   |
| 1321                  | 32                  | 1017                  |
| 1321                  | 36                  | 1141                  |
| 1321                  | 40                  | 1264                  |
| 1321                  | 45                  | 1416                  |
| 1321                  | 50                  | 1567                  |
| 1321                  | 55                  | 1717                  |
| 1321                  | 60                  | 1866                  |
| 1321                  | 65                  | 2013                  |
| 1524                  | 6.3                 | 236                   |
| 1524                  | 7.1                 | 266                   |
| 1524                  | 8                   | 299                   |
| 1524                  | 8.8                 | 329                   |
| 1524                  | 10                  | 373                   |
| 1524                  | 11                  | 410                   |
| 1524                  | 12.5                | 466                   |
| 1524                  | 14.2                | 529                   |
| 1524                  | 16                  | 595                   |
| 1524                  | 17.5                | 650                   |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 1524                  | 20                  | 742                   |
| 1524                  | 22.2                | 822                   |
| 1524                  | 25                  | 924                   |
| 1524                  | 28                  | 1033                  |
| 1524                  | 30                  | 1105                  |
| 1524                  | 32                  | 1177                  |
| 1524                  | 36                  | 1321                  |
| 1524                  | 40                  | 1464                  |
| 1524                  | 45                  | 1641                  |
| 1524                  | 50                  | 1818                  |
| 1524                  | 55                  | 1993                  |
| 1524                  | 60                  | 2166                  |
| 1524                  | 65                  | 2339                  |
| 1727                  | 7.1                 | 301                   |
| 1727                  | 8                   | 339                   |
| 1727                  | 8.8                 | 373                   |
| 1727                  | 10                  | 423                   |
| 1727                  | 11                  | 466                   |
| 1727                  | 12.5                | 529                   |
| 1727                  | 14.2                | 600                   |
| 1727                  | 16                  | 675                   |
| 1727                  | 17.5                | 738                   |
| 1727                  | 20                  | 842                   |
| 1727                  | 22.2                | 933                   |
| 1727                  | 25                  | 1049                  |
| 1727                  | 28                  | 1173                  |
| 1727                  | 30                  | 1256                  |
| 1727                  | 32                  | 1338                  |
| 1727                  | 36                  | 1501                  |
| 1727                  | 40                  | 1664                  |
| 1727                  | 45                  | 1867                  |
| 1727                  | 50                  | 2068                  |
| 1727                  | 55                  | 2268                  |
| 1727                  | 60                  | 2467                  |
| 1727                  | 65                  | 2664                  |
| 1930                  | 8                   | 379                   |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 1930                  | 8.8                 | 417                   |
| 1930                  | 10                  | 474                   |
| 1930                  | 11                  | 521                   |
| 1930                  | 12.5                | 591                   |
| 1930                  | 14.2                | 671                   |
| 1930                  | 16                  | 755                   |
| 1930                  | 17.5                | 825                   |
| 1930                  | 20                  | 942                   |
| 1930                  | 22.2                | 1044                  |
| 1930                  | 25                  | 1175                  |
| 1930                  | 28                  | 1313                  |
| 1930                  | 30                  | 1406                  |
| 1930                  | 32                  | 1498                  |
| 1930                  | 36                  | 1682                  |
| 1930                  | 40                  | 1864                  |
| 1930                  | 45                  | 2092                  |
| 1930                  | 50                  | 2318                  |
| 1930                  | 55                  | 2543                  |
| 1930                  | 60                  | 2767                  |
| 1930                  | 65                  | 2990                  |
| 2134                  | 8.8                 | 461                   |
| 2134                  | 10                  | 524                   |
| 2134                  | 11                  | 576                   |
| 2134                  | 12.5                | 654                   |
| 2134                  | 14.2                | 742                   |
| 2134                  | 16                  | 836                   |
| 2134                  | 17.5                | 913                   |
| 2134                  | 20                  | 1043                  |
| 2134                  | 22.2                | 1156                  |
| 2134                  | 25                  | 1300                  |
| 2134                  | 28                  | 1454                  |
| 2134                  | 30                  | 1557                  |
| 2134                  | 32                  | 1659                  |
| 2134                  | 36                  | 1863                  |
| 2134                  | 40                  | 2066                  |
| 2134                  | 45                  | 2318                  |

Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 2134                  | 50                  | 2570                  |
| 2134                  | 55                  | 2820                  |
| 2134                  | 60                  | 3069                  |
| 2134                  | 65                  | 3317                  |
| 2337                  | 10                  | 574                   |
| 2337                  | 11                  | 631                   |
| 2337                  | 12.5                | 717                   |
| 2337                  | 14.2                | 813                   |
| 2337                  | 16                  | 916                   |
| 2337                  | 17.5                | 1001                  |
| 2337                  | 20                  | 143                   |
| 2337                  | 22.2                | 1267                  |
| 2337                  | 25                  | 1425                  |
| 2337                  | 28                  | 1594                  |
| 2337                  | 30                  | 1707                  |
| 2337                  | 32                  | 1819                  |
| 2337                  | 36                  | 2043                  |
| 2337                  | 40                  | 2266                  |
| 2337                  | 45                  | 2544                  |
| 2337                  | 50                  | 2820                  |
| 2337                  | 55                  | 3095                  |
| 2337                  | 60                  | 3369                  |
| 2337                  | 65                  | 3642                  |
| 2438                  | 10                  | 599                   |
| 2438                  | 11                  | 658                   |
| 2438                  | 12.5                | 748                   |
| 2438                  | 14.2                | 849                   |
| 2438                  | 16                  | 956                   |
| 2438                  | 17.5                | 1045                  |
| 2438                  | 20                  | 193                   |
| 2438                  | 22.2                | 1323                  |
| 2438                  | 25                  | 1488                  |
| 2438                  | 28                  | 1664                  |
| 2438                  | 30                  | 1782                  |
| 2438                  | 32                  | 1899                  |
| 2438                  | 36                  | 2133                  |



Pipe Weight Chart for ISO 4200 table 2 Series 2  
(tubes for general purpose use)

| Outside Diameter (mm) | Wall Thickness (mm) | Plain End Mass (kg/m) |
|-----------------------|---------------------|-----------------------|
| 2438                  | 40                  | 2366                  |
| 2438                  | 45                  | 2656                  |
| 2438                  | 50                  | 2945                  |
| 2438                  | 55                  | 3232                  |
| 2438                  | 60                  | 3519                  |
| 2438                  | 65                  | 3804                  |

Botop Steel